

PRODUCTS SPECIFICATION OF SULPHUR

Product No. 1: Micronized Sulphur Powder

PROPERTY & COMPOSITION	SPECIFICATION
Purity (WT%) Min.	99.8
Ash Content (WT%) Max.	0.06
Organic Matter (WT%) Max.	0.07
Moisture (WT%) Max.	0.4
Color	Light Yellow
Form	Micronized Powder
Mesh Size	Grade 200 – 500 According To Order

Product No. 2: Granular Sulphur

PROPERTY & COMPOSITION	SPECIFICATION
Purity (WT%) Min.	99.5
Form	Granular
Ash Content (WT%) Max.	0.05
Moisture (WT%) Max.	0.5
Color	Yellow
Acidity, H ₂ SO ₄ (WT%) Max.	0.02
Carbon Content (WT%) Max.	0.03

Product No. 3: Sulphur Coated Urea

PROPERTY & COMPOSITION	SPECIFICATION
Nitrogen Content (WT%)	36
Sulphur (WT%)	15
Additive (WT%)	5
Moisture (WT%)	0.5
Main Size (WT%) 2-4mm	92

Product No. 4: Sulphur Bentonite

PROPERTY & COMPOSITION	SPECIFICATION
Sulphur Content (WT%)	Min. 85 Max. 91
Bentonite Content (WT%)	Min. 9 Max. 15
Moisture Content (WT%) Max.	0.5
Form	Pastille (Half Sphere)
Color	Yellow Green – Earth Tone
Size	Min. 75% between 2 & 5 mm Less than 0.3 mm <1%

